Safety Data Sheet (SDS)

Revision Number: 4.0		Last updated	24 July 2019
1. Product and Company Identification	<u>on</u>		
Product Name:	[Cit17] - Histone H3 (1 - 21) - GGK(Biotin)		
	ARTKQTA	RKSTGGKAP - Cit - KQLAGG -	- K(Biotin)
Manufacturer/Supplier:	AnaSpec, Ir	ic.	
	www.anaspec.com		
	34801 Campus Drive		
	Fremont, CA 94555		
	Tel: 510-791-9560		
	Fax: 510-791-9572		
	Email: servi	ce@anaspec.com	
	Kaneka Eur	ogentec SA,	
		Saint Jean 5 4102 Seraing Belgiu	ım
	Tel. +32-4-3		
	Fax. +32-4-	3727500	
	E-mail info	@eurogentec.com	
	Kaneka Eur	ogentec Helpdesk	
	Tel. +32-4-3	<del>-</del>	
Catalog Number	AS-65233-1		
Relevant identified uses of the substance/preparation and uses advised against	For laborate	ory use only.	
Emergency information		act the regional Eurogentec represe Kaneka Eurogentec S.A. directly (	
2. Hazards Identification			
Emergency Overview: We do re	dling chemicals	dling all chemicals with caution. Use . To our knowledge, the hazards of this r	
		ance according to the GHS angerous substance according to the GHS	S
GHS Signal Words: None			
GHS Hazard Statements: None			

GHS Precautionary Statements: None

Potential Health Effects for:

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Good hygiene practice requires that exposure be kept to a minimum and that suitable control

measures be used in an occupational setting.

Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Skin: In case of contact, immediately wash skin with soap and copious amount of water.

Eyes: In case of contact, immediately flush eyes with copious amounts of water for at least 15 minutes.

Chronic Exposures: No information available. We recommend limiting prolonged exposure.

Target Organs: No information available

HMIS Classification

Health hazard: 0

Chronic Health Hazard: 0

Flammability: 0
Physical hazards: 0

NFPA Rating

Health hazard: 0

Fire: 0

Reactivity Hazard: 0

#### 3. Composition

*Ingredients/Components:* 

Chemical Name: [Cit17] - Histone H3 (1 - 21) - GGK(Biotin)

ARTKQTARKSTGGKAP - Cit - KQLAGG - K(Biotin)

Molecular formula: NA Molecular weight: 2724.2

CAS-No NA EC-No NA

#### 4. First Aid Measures

I. I I i	If done is intent done	form contouring to do one
Inhalation:		
	Encourage patient to blow nose to ensure clear passage of breathing.  If irritation or discomfort persists seek medical attention.	
		<del>-</del>
maintain open airway an		
		patient forward or place on left side (head-down position, if possible) to
		1 1
	Observe the patient caref	
	Give water to rinse out m	outh, then provide liquid slowly and as much as casualty can comfortably
	drink.	
	Seek medical advice.	
Skin:	If skin or hair contact occ	zurs:
	Flush skin and hair with r	running water (and soap if available).
Seek medical attention in		
Eyes:	If this product comes in c	ontact with the eyes:
	Wash out immediately wi	
Ensure complete irrigation		n of the eye by keeping eyelids apart and away from eye and moving the
		fting the upper and lower lids.
	If pain persists or recurs s	
	pull persists of recurs s	
5 Fine Fight	ing Measures	
Extinguishing	media:	Water spray or fog.
		Alcohol resistant foam.
		Dry chemical powder.
		BCF (where regulations permit).
		Carbon dioxide
Special firefig	hting procedures:	Alert Emergency Responders and tell them location and nature of
Special filefis	ming procedures.	hazard.
		Wear breathing apparatus plus protective gloves.
		Prevent, by any means available, spillage from entering drains or water
		course.
		Use water delivered as a fine spray to control fire and cool adjacent
		area.
		<b>DO NOT</b> approach containers suspected to be hot.
		Cool fire exposed containers with water spray from a protected location.
		If safe to do so, remove containers from path of fire.
		Equipment should be thoroughly decontaminated after use.
Unusual fire a	and explosions hazards:	Emits toxic fumes under fire conditions
		.1
6. Accidenta	l Release Measures	
Spill response	Remove al	l ignition sources.
		Il spills immediately.
		tact with skin and eyes.
		rsonal contact by using protective equipment.
		ean up procedures and avoid generating dust.
		suitable, labeled container for waste disposal
Containment		
Comainment		personal contact, including inhalation.
		ective clothing when risk of exposure occurs.
	Use in a w	ell-ventilated area.

	DO NOT enter confined spaces until atmosphere has been checked.  DO NOT allow material to contact humans, exposed food or food utensils.  Avoid contact with incompatible materials.  When handling, DO NOT eat, drink or smoke.  Keep containers securely sealed when not in use.
	Avoid physical damage to containers.  Always wash hands with soap and water after handling.
	Use good occupational work practice. Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.  Do NOT cut, drill, grind or weld such containers
PPE	Use personal protective equipment
Store at -20°C, dry des	siccated and protected from light. Store away from oxidizing agent.
8. Exposure Controls	
	/ Personal Protection  Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by
8. Exposure Controls	/ Personal Protection  Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
8. Exposure Controls	/ Personal Protection  Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.  Exhaust ventilation should be designed to prevent accumulation and re-circulation of
8. Exposure Controls	/ Personal Protection  Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.  Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace.  If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
8. Exposure Controls	/ Personal Protection  Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.  Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace.  If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:  (a): particle dust respirators, if necessary, combined with an absorption cartridge;  (b): filter respirators with absorption cartridge or canister of the right type;
8. Exposure Controls	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.  Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace.  If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:  (a): particle dust respirators, if necessary, combined with an absorption cartridge;  (b): filter respirators with absorption cartridge or canister of the right type;  (c): fresh-air hoods or masks  Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
8. Exposure Controls	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.  Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace.  If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:  (a): particle dust respirators, if necessary, combined with an absorption cartridge;  (b): filter respirators with absorption cartridge or canister of the right type;  (c): fresh-air hoods or masks  Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.  Powder handling equipment such as dust collectors, dryers and mills may require
8. Exposure Controls	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.  Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace.  If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:  (a): particle dust respirators, if necessary, combined with an absorption cartridge;  (b): filter respirators with absorption cartridge or canister of the right type;  (c): fresh-air hoods or masks  Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.

# 9. Physical and Chemical Properties

Physical State	White Powder
Odour	Not available
Solubility in Water	Not available
Specific Gravity	Not available
рН	Not available
Boiling Point	Not available
Melting Point	Not available
Flash Point	N/A
Vapor Pressure:	N/A
Vapor Density:	N/A

10. Stability and Reactivity	
Thermal Decomposition	No data available
Dangerous Products of Decomposition	No data available
Dangerous Reactions	COx, NOx when burned

Keep container tightly closed in a dry well-ventilated place. Store in -20 °C, dry refrigerator.

## 11. Toxicological Information

RTECS Number	N/A
Toxicity	No information available.
Health Hazards	Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
Potential Hazards	Not available
Carcinogenicity:	No significant acute toxicological data identified
OSHA Permissible Exposure Limit(PEL) Data	N/A
ACGIH Threshold Limit Values (TLV)	N/A

Reproductive Toxicity:

No information available

## 12. Ecological Information

No information available.

# 13. Disposal Considerations

All waste must be handled in accordance with local, state and federal regulations. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

## 14. Transport Information

Hazard Class	N/A
Identification Number	N/A
Packing Group	N/A
Proper Shipping Name (DOT)	N/A

# 15. Regulatory Information

California Proposition 65: N/A

US TSCA (Toxic Substance Control Act): N/A

US CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act: N/A

US SARA Title III (Superfund Amendments and Reauthorization Act: N/A

US Other: N/A

EC EINICS (European Inventory of Existing Commercial Chemical Substances) Number: N/A

EC Risk Statements: N/A

Other Country Regulations: N/A

#### 16. Other Information

It is not intended for food, drug, household, agricultural or cosmetic use. A technically qualified individual experienced in handling potentially hazardous chemicals must supervise its use. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Users should make independent decisions regarding completeness of the information based on all sources available. AnaSpec shall not be held liable for any damage resulting from handling or from contact with the above product.